



SDF-310

10.4” Standalone Digital Fishfinder (1-3kW)

(Installation & operation manual)

Contents

| | |
|---|----|
| 1. Cautions for safety | 6 |
| 1. Before operate the equipment (Safety warning) | 7 |
| 2. Before handle cables (Safety instruction)..... | 8 |
| 3. Before handle the vibrator and water temperature sensor..... | 8 |
| 4. Precautions | 9 |
| 2. Specifications | 10 |
| 1. Tx, Rx Specifications | 11 |
| 2. Specification of display unit..... | 11 |
| 3. Display functions | 12 |
| 4. Component | 13 |
| 3. Discription | 14 |
| 1. Display discription | 15 |
| 2. Power ON/OFF..... | 16 |
| 3. Menu..... | 17 |
| 4. Display mode | 19 |
| 4. Functions | 20 |
| 1. SONAR..... | 21 |
| 1.1 Tx Power | 21 |
| 1.2 Tx Rate | 21 |
| 1.3 Pulse Edge | 22 |
| 1.4 Pulse Length..... | 22 |
| 1.5 Frequency Setting..... | 23 |
| 1.6 Frequency Adjust..... | 23 |
| 1.7 Tx Fix..... | 24 |
| 1.8 Bottom Search | 24 |
| 1.9 Trigger Sweep..... | 25 |
| 2. Display..... | 26 |
| 2.1 Mode | 26 |
| 2.2 Range | 26 |
| 2.3 Auto Range | 27 |
| 2.4 Display Speed | 27 |
| 2.5 Interference/Noise Reduction | 28 |

| | |
|---------------------------------|----|
| 2.6 Refresh Area | 28 |
| 2.7 TVG | 29 |
| 2.7.1 TVG level setting | 29 |
| 2.7.2 TVG distance setting..... | 29 |
| 2.8 STC | 30 |
| 2.9 Gain Offset | 30 |
| 2.10 Auto Gain Offset | 31 |
| | |
| 3. Color | 32 |
| 3.1 Day/Night | 32 |
| 3.2 Colors | 32 |
| 3.3 Hue | 33 |
| 3.4 Background | 33 |
| 3.5 Color Erase | 34 |
| 3.6 Clutter | 34 |
| 3.7 White Line | 35 |
| 3.8 White Line Color | 35 |
| 3.9 Temperature Color | 36 |
| | |
| 4. View | 37 |
| 4.1 Direction | 37 |
| 4.2 Division | 37 |
| 4.3 A-Scope | 38 |
| 4.4 Depth Size | 38 |
| 4.5 Depth Scale | 39 |
| 4.6 help | 39 |
| 4.7 Color Table | 40 |
| 4.8 Temperature Graph | 40 |
| 4.9 Detection Area | 41 |
| 4.10 Header Info | 41 |
| 4.11 Units | 42 |

| | |
|------------------------|----|
| 5. Alarm | 43 |
| 5.1 Alarm | 43 |
| 6. Etc | 44 |
| 6.1 Language | 44 |
| 6.2 Key Beep | 44 |
| 6.3 Function Key | 44 |
| 6.4 Push Button | 45 |
| 6.5 Simulation | 45 |
| 7. Zoom | 46 |
| 7.1 Zoom Mode | 46 |
| 7.2 Zoom Start..... | 46 |
| 7.3 Zoom End | 46 |
| 7.4 Zoom Length | 46 |
| 8. Fish | 47 |
| 8.1 View Fish | 47 |
| 8.2 Fish filter | 47 |
| 8.3 Fish Gain..... | 47 |
| 9. NEMA | 48 |
| 9.1 NEMA Output..... | 48 |
| 9.2 UART1 | 48 |
| 9.3 UART2 | 48 |
| 9.4 UART Monitor..... | 48 |
| 10. Calibration..... | 49 |
| 10.1 Temperature | 49 |
| 10.2 Voltage | 49 |

| | |
|--|-----------|
| 10.3 Beam Angle | 49 |
| 5. Connecting other devices | 50 |
| 1. Installation | 51 |
| 2. Cable connection..... | 52 |
| 3. Rear Connector Pinout..... | 53 |
| 4. Power Cable Connection | 54 |
| 6. Maintenance and Troubleshooting | 55 |
| 1. Maintenance | 56 |
| 2. Troubleshooting | 57 |
| Appendix : Product outline drawing..... | 59 |

1

Cautions for safety



This chapter explains precautions to prevent incidents may be caused by user or environmental factor of this equipment.

1. Before operate the equipment (Safety warning)

Caution

- Hazardous voltage exists inside the equipment.
- Do not disassemble or reorganize this equipment except of approved technician.
There is risk of electric shock.
- Please contact our A/S center for repair.

Warning

- Install the equipment based on formal install method. Installation by Simple method may cause accident include personal injury.
- The information displayed on this equipment cannot be used as source of sail. It can be a reason of distress.
★ A formal chart must be used when determine of sailing.
- Do not turn on the power in a place with flammable material such as gas. It can be a reason of fire.
- Use of unapproved power can cause fire.
- Do not disassemble or reorganize the equipment. It can cause fire, electrical shock and injury.
- Never operate the equipment with wet hand. It can cause electrical shock or injury.
- Turn off the power immediately when equipment is out of order or emit smoke. Otherwise can cause fire or electrical shock.

Warning

- Do not install on a place with rain or water spray. It can cause fire or electric shock.
- Do not install in a place of high temperature. Rise of internal temperature of the equipment can cause fire, injury and electric shock.
- The equipment must be grounded after installation. If not grounded properly, can be interfered by other equipment or affect to other.
- Install at the place without direct sunlight to prevent drop of visibility and heating the equipment.

2. Before handle cables (Safety instruction)

Caution

- Use the regular power code to prevent heating and fire.
- Do not leave the equipment as unplugged. Wet plug become short circuit and cause of heating and fire.
- Install the cables to not interfere steering. If foot or steering device are caught it cause incident.
 - ★ Do not put heavy thing on the cable or bend the cable excessively.
- Do not disassemble or reorganize the code. It can cause heating, fire and electrical shock.
- Do not use damaged code. It can cause fire or electrical shock.

Warning

- Do not pull the cable when unplug.
 - ★ Holding the plug body and pull.
- Be careful not to pinch the cables when install.

3. Before handle the vibrator and water temperature sensor

Danger

- Operation on the ocean is very unstable and dangerous. Installation or repair of the vibrator or water temperature sensor should be done on the land, after fix the vessel body securely. Otherwise, severe injury can be caused.

Warning

- Ventilate enough the cabin when use solvent such as glue. Volatile gas of solvent can result poisoning.
- Do not unplug or insert the code of vibrator while the equipment is turned on. It can cause electrical shock or disorder.
- Do not use electrical tool with wet hand. It can cause electrical shock.
- Do enough water proof process after installation of thru-hull equipment. If not, it can cause water leaking and distress.

4. Precautions

1. Turn the power off when start engine.

Rapid change of battery voltage is occurred when start engine and it cause bad effect to equipment.

2. Power supply: 12-35VDC

This equipment should be used in range of power 12~35VDC.

3. Do not use solvent.

The main equipment is made by plastic and coated. Do not use solvents like thinner or alcohol on it. To remove dirt, wipe with soft fabric soaked in water or neutral detergent after squeeze enough.

2

Specification



This chapter explains about specification of this equipment.

- TX/RX specification
- Specification of display unit
- Functional specification
- Component

1. TX/RX specification

TX frequency and output

- Frequency : Select two among 28 / 38 / 50 / 68 / 82 / 88 / 107 / 150 / 200 KHz
- TX output : 1 / 2 / 3KW , Transmit by turns
- Power reduction : Auto/ 1~10
- TX pulse length : Short1 , Short2 , Standard , Long
0.05~5.0 msec when operation manually
- Frequency tuning : 5~10% of each TX frequency
- Amplifier : High dynamic range

2. Specification of display unit

Specification

- LCD : 10.4inch
- Resolution : 600 x 800
- Brightness : 500 cd/m²
- Power supply : 12V to +35V DC Approx. 50W
- Weight & dimension : 5.2Kg , 307mm X 321.5mm X 135.3mm
(Width X Length X Height)

Operation environment

- Temperature : Main equipment = -15°C~+55°C
- Humidity : Less than 93% (+30°C~+60°C)

3. Functional specification

Display

- Display color : 8 / 16 / 64 ,
Background: selectable among 5 colors
- Range : 5~3000m, Shift : 0~2000m
Extension range : 5~200m of whole range
- Display mode : Single, Dual, Extension Dual, A-scope
- Zoom mode : Bottom lock, Bottom zoom, Marker zoom
- Speed : x4 , x2 , x1 , 1/2 , 1/4 , 1/8 , Stop
- Alarm : Water depth, Fish, Water temperature
- Noise reduction : Off, Light, Medium, Strong or Frequency adjustment
(Range depends on transducer)
- Auto display : Auto gain (fishing/sailing), Auto depth,
Water temp. graph, Battery voltage, Water
temp., Display speed

Interface

- Number of port : NMEA0183 Ver1.5/ 2.0 / 3.0 (I/O) -2 port
- Input data : Will be updated
- Output data : DPT, Will be updated for the rests

4. Component

■ SDF-310 Fish finder

| No. | Description | Part number | Q/ty | Remark |
|-----|------------------------|---------------------------|---------|--|
| 1 | Main unit | SDF-310 | 1EA | |
| 2 | DC cable | SCN3-5M-FUSE Cable Ass'y | 1EA | |
| 3 | Fuse | DC+(24V)/5A , DC-(24V)/7A | 1EA/1EA | |
| 4 | Spare fuse | 24V/5A , 12V/7A | 3EA/3EA | |
| 5 | DATA connector | SCN-16-7P | 1EA | |
| 6 | Transducer connector | SCK-25-8P | 1EA | When connect with own transducer of vessel |
| 7 | Installation accessory | | 1SET | |
| 8 | Operation manual | | 1EA | |
| 9 | Easy manual | | 1EA | |
| | | | | |
| | | | | |

+

3


Description



This chapter explains about SDF-310 equipment and display.

- Display description**
- Power ON/OFF**
- Menu tree**
- Screen mode**


1 Display description



| No. | Key/Button | Description |
|-----|-------------|--|
| 1 | Adjust gain | Gain-High : Adjust High frequency. Gain-low : Adjust low frequency. Push the button : change the gain mode auto or manual. In manual mode, rotate the button to left : decrease the level , to right : increased the level. |
| 2 | Shift/Range | Adjust by using ▲ or ▼ . (This function is not available in Auto shift , Auto range mode) |
| 3 | Menu/ESC | Open/Close the menu Escape from current operation. |
| 4 | Func | Please read 6.3 Func key . |
| 5 | Cursor | Move in the menu list. Set the level of adjustment Move VRM marker. |
| 6 | Screen | Choose the screen to display. |
| 7 | Enter | Choose and apply the menu. Open the next submenu list. At Fish finder screen : Show screenshot image (maximum 10 images) |
| 8 | Mark | Input waypoint |
| 9 | Power | Short press : Turn the power on / Open the Brightness setting menu. Long press : Turn the power off. |

2 Power ON/OFF

■ Power ON

Press the  button. About 2 seconds later, Samyung company logo is displayed and fish finder is available.

■ Power OFF

Press and hold  button for 5 seconds.







3 Menu tree

| | |
|-----------------|-----------------------|
| 1. SONAR | 1. TX Power |
| | 2. TX Rate |
| | 3. Pulse Edge (L) |
| | 4. Pulse Edge (H) |
| | 5. Pulse Length (L) |
| | 6. Pulse Length (H) |
| | 7. Freq. Setting (L) |
| | 8. Freq. Setting (H) |
| | 9. Freq. Adjust (L) |
| | 10. Freq. Control (H) |
| | 11. TX Fix |
| | 12. Bottom Search |
| | 13. Trigger Sweep |

| | |
|-----------------|----------------------|
| 2. DISP. | 1. Mode |
| | 2. Range |
| | 3. Auto Range |
| | 4. Display Speed |
| | 5. Interference |
| | 6. Noise Reduction |
| | 7. Refresh Area |
| | 8. TVG |
| | 9. STC |
| | 10. Gain Offset |
| | 11. Auto Gain Offset |

| | |
|-----------------|---------------------|
| 3. COLOR | 1. Day/Night |
| | 2. Color |
| | 3. Hue |
| | 4. Background |
| | 5. Color Erase |
| | 6. Clutter |
| | 7. White Line |
| | 8. White Line Color |
| | 9. Temp. Color |


| | |
|----------------|-------------------|
| 4. VIEW | 1. Direction |
| | 2. Division |
| | 3. A-scope |
| | 4. Depth Size |
| | 5. Depth Scale |
| | 6. Help |
| | 7. Color Table |
| | 8. Temp. Graph |
| | 9. Detection Area |
| | 10. Header Info |
| | 11. Units (Depth) |
| | 12. Units (Temp.) |



4 Screen Mode

The fish finder provide unique display mode for each mode.
Press Screen button to select a desired screen mode.

- Screen mode switch



4

Functions



This chapter explains the functions of SDF-310

- Sonar
- Image
- Color
- Display
- Alarm
- Others
- User

1. Sonar

1.1 Transmitting (Tx)Power

If same frequency is used by near vessel's fish finder, there could be interference noise in the display. If there is an anyway to reduce other's fish finder's output then the interference noise can be suppressed. The transmitting power can be adjusted manually and it can be changed automatically. If you want to stop the transmitting, select stop.

| | |
|----------------------------|-------------|
| 1. Tx Power | Off |
| 2. Tx Rate | Min |
| 3. Pulse Edge(L) | 1 |
| 4. Pulse Edge(H) | 2 |
| 5. Pulse Length(L) | 3 |
| 6. Pulse Length(H) | 4 |
| 7. Freq. Setting(L) | 5 |
| 8. Freq. Setting(H) | 6 |
| 9. Freq. Adjust(L) | 7 |
| 10.Freq. Adjust(H) | 8 |
| 11.Tx Fix | 9 |
| 12.Bottom Search | 10 |
| 13.Trigger Sweep | Auto |

Transmitting (Tx) power setup

menu ➔ Select [Sonar] ➔ Select [Tx Power] ➔ Select desired power

1.2 Transmitting (Tx) Speed

You can select transmitting speed. If you select smaller speed, the transmitting interval is getting longer and the display time is getting long.

| | |
|----------------------------|-----------------|
| 1. Tx Power | 5 |
| 2. Tx Rate | 1 |
| 3. Pulse Edge(L) | 2 |
| 4. Pulse Edge(H) | 3 |
| 5. Pulse Length(L) | 4 |
| 6. Pulse Length(H) | 5 |
| 7. Freq. Setting(L) | Max |
| 8. Freq. Setting(H) | 200KHz |
| 9. Freq. Adjust(L) | 50.0KHz |
| 10.Freq. Adjust(H) | 200.0KHz |
| 11.Tx Fix | LF |
| 12.Bottom Search | LF |
| 13.Trigger Sweep | Off |

Setting for Transmitting (Tx) Speed

menu ➔ Select [Sonar] ➔ Select [Tx rate] ➔ Select desired speed

1.3 High resolution pulse

If you set it ON then, you can reduce your interference on other vessel.

Setting for low frequency pulse edge

menu ➔ Select [Sonar] ➔ Select [pulse edge(L)] (Select 『On or off』)

Setting for high frequency pulse edge

menu ➔ Select [Sonar] ➔ Select [pulse edge(H)] (Select 『On or off』)

1.4 Pulse Width

The pulse width is changing depending on range and Shift but it could be set by manually. If you set short pulse range, you can have better image and if you set long pulse range, you can see deeper

If you want to have better image, set short1, short2.

Short1 : You can have a better Image but less depth compare to short2.

Short2 : You can have better target image in short depth.

Standard : In general, this can use used for various fish search

long : Target image is not clear but search distance is longer.

| | |
|---------------------|---------|
| 1. Tx Power | 5 |
| 2. Tx Rate | Max |
| 3. Pulse Edge(L) | Off |
| 4. Pulse Edge(H) | Off |
| 5. Pulse Length(L) | Short1 |
| 6. Pulse Length(H) | Short2 |
| 7. Freq. Setting(L) | Std. |
| 8. Freq. Setting(H) | Long |
| 9. Freq. Adjust(L) | 0.05 ms |
| 10. Freq. Adjust(H) | 0.1 ms |
| 11. Tx Fix | 0.2 ms |
| 12. Bottom Search | 0.4 ms |
| 13. Trigger Sweep | 0.6 ms |
| | 0.8 ms |
| | 1.0 ms |
| | 1.5 ms |
| | 2.0 ms |
| | 2.5 ms |
| | 3.0 ms |
| | 3.5 ms |
| | 4.0 ms |
| | 4.5 ms |
| | 5.0 ms |

Setting for Low frequency pulse edge


menu ➔ Select [Sonar] ➔ Select [Pulse edge(L)] (Select 『On or off』)

Setting for high Frequency pulse edge

menu ➔ Select [Sonar] ➔ Select [Pulse edge(H)] (Select 『On or off』)

1.5 Frequency setting

Select a frequency to be displayed in high and low frequency screen.



<Frequency selection menu>

□ Setting for Low frequency


menu → Select [Sonar] → Select [Freq. Setting(L)] → Change to a desired value □

□ Setting for high frequency


menu → Select [Sonar] → Select [Freq. Setting(H)] → Change to a desired value

1.6 Frequency adjust

1.5 You can do fine tune the selected frequency in the frequency selection



<When select low frequency 88KHz>



< When select high frequency 200KHz >

□ Setting for Low frequency

menu → Select [Sonar] → Select [Frequency adjust (L)] → Change to a desired value

□ Setting for High frequency

menu → Select [Sonar] → Select [Frequency adjust (H)] → Change to a desired value

1.7 Fixed Transmission (Tx Fix)

Below is the transmission/receiving fixed type according to transducers.

- Low frequency: transmit and receive low frequency & high frequency in order using the low frequency transmitter.
- High frequency: transmit and receive low frequency & high frequency in order using the high frequency transmitter.
- OFF : Use all low and high frequency transmitter in order.
Low frequency use low frequency transmitter and high frequency use high frequency transmitter.

- Low frequency or high frequency setup can be set when a transducer is connected to single line (two lines, shield)
- OFF setup can be set when a transducer is connected to dual line (four lines, shield) or when low frequency transducer and high frequency transducer is used separately.
- Above setup need to be set by authorized distributor.

| | |
|---------------------|----------|
| 1. Tx Power | 5 |
| 2. Tx Rate | Max |
| 3. Pulse Edge(L) | Off |
| 4. Pulse Edge(H) | Off |
| 5. Pulse Length(L) | Std. |
| 6. Pulse Length(H) | Std. |
| 7. Freq. Setting(L) | 50KHz |
| 8. Freq. Setting(H) | 200KHz |
| 9. Freq. Adjust(L) | 50.0KHz |
| 10.Freq. Adjust(H) | 200.0KHz |
| 11.Tx Fix | Off |
| 12.Bottom Search | LF |
| 13.Trigger Sweep | HF |

❑ Setting for Fixed transmitting

menu ➔ Select [Sonar] ➔ Select [Tx Fix] ➔ Select a desired fixed transmitting frequency

1.8 Depth Calculation Frequency

Frequency which can display the depth of water in the screen can be selected. If automatic is selected, low frequency's depth is display preferentially

❑ Setting for Depth Calculation frequency

menu ➔ Select [Sonar] ➔ Select [bottom search] ➔ Select a desired frequency

1.9 Trigger Sweep

This can reduce electrical interference noise of other vessel by transiting signal irregularly

Setting for Trigger Sweep

menu ➔ Select [Sonar] ➔ Select [Trigger Sweep] ➔ (Select 『ON/OFF』)

2. Display

2.1 Mode

It can set a screen display mode.


| | |
|-----------------------------|--------|
| 1. Mode | L/H |
| 2. Range | L |
| 3. Auto Range | H |
| 4. Display Speed | Zoom/L |
| 5. Interference | Zoom/H |
| 6. Noise Reduction | Off |
| 7. Refresh Area | All |
| 8. TVG | |
| 9. STC | |
| 10. Gain Offset | |
| 11. Auto Gain Offset | |

Setting for Mode selection

menu ➔ Select [Display] ➔ Select [Mode] ➔ Select a desired display mode

2.2 Range

Range value can be changed by shift key and range key.



Setting for Range setup

menu ➔ Select [Display] ➔ Select [Range] ➔ Select a desired range value

2.3 Auto Range

Range can be adjusted manually or automatically.

Automatic adjustment is useful when you are preoccupied with other tasks and do not have the time to adjust the display.

| | |
|-----------------------------|-------------------|
| 1. Mode | L |
| 2. Range | 25m |
| 3. Auto Range | Off |
| 4. Display Speed | Auto Range |
| 5. Interference | Off |
| 6. Noise Reduction | Off |
| 7. Refresh Area | All |
| 8. TVG | |
| 9. STC | |
| 10. Gain Offset | |
| 11. Auto Gain Offset | |

□ Setting range

menu ➔ select [display] ➔ select [auto range] ➔ (select among 『off/auto range』)

2.4 Display speed

The picture advance speed determines how quickly the vertical scan lines run across the screen. When choosing a picture advance speed, keep in mind that a fast advance speed will expand echoes horizontally on the screen and a slow advance speed will contract them. A fast advance speed is useful for observing the rugged bottom closely. A slow advance speed is useful for observing the smooth bottom. (Maximum speed X 8 , Minimum Speed X 1/8)

| | |
|-----------------------------|-------------------------------|
| 1. Mode | L |
| 2. Range | 25m |
| 3. Auto Range | Off |
| 4. Display Speed | x4 |
| 5. Interference | x2 |
| 6. Noise Reduction | x1 |
| 7. Refresh Area | x ¹ / ₂ |
| 8. TVG | x ¹ / ₄ |
| 9. STC | x ¹ / ₈ |
| 10. Gain Offset | STOP |
| 11. Auto Gain Offset | |

□ Setting for display speed

menu ➔ select [display] ➔ select [display speed] ➔ select desired speed

2.5 Interference

Their induced noise from the electric apparatus and the occurrence of periodic interference from the lineup of a fish finder is the ability to eliminate noise.

| | |
|----------------------|--------|
| 1. Mode | L |
| 2. Range | 25m |
| 3. Auto Range | Off |
| 4. Display Speed | x1 |
| 5. Interference | Off |
| 6. Noise Reduction | Low |
| 7. Refresh Area | Medium |
| 8. TVG | High |
| 9. STC | |
| 10. Gain Offset | |
| 11. Auto Gain Offset | |

< Interference >

| | |
|----------------------|-----|
| 1. Mode | L |
| 2. Range | 25m |
| 3. Auto Range | Off |
| 4. Display Speed | x1 |
| 5. Interference | Off |
| 6. Noise Reduction | Off |
| 7. Refresh Area | On |
| 8. TVG | |
| 9. STC | |
| 10. Gain Offset | |
| 11. Auto Gain Offset | |

< noise reduction >

❑ Setting for interference

menu ➔ select [display] ➔ select [interference] ➔ select desired level

❑ Setting for noise reduction

menu ➔ select [display] ➔ select [noise reduction] ➔ select among 『off/on』

2.6 Refresh area

Change from the current value, whether, as a whole should choose.

| | |
|----------------------|----------|
| 1. Mode | L |
| 2. Range | 25m |
| 3. Auto Range | Off |
| 4. Display Speed | x1 |
| 5. Interference | Off |
| 6. Noise Reduction | Off |
| 7. Refresh Area | All |
| 8. TVG | From Now |
| 9. STC | |
| 10. Gain Offset | |
| 11. Auto Gain Offset | |

❑ Setting for refresh area

menu ➔ select [display] ➔ select [refresh area] ➔ (select among 『all/from now』)

2.7 TVG

A fish school at a deep depth is displayed in weak colors even if it is equal in strength to one in shallow waters. This is due to propagation attenuation of the ultrasonic wave. To compensate for this difference, use TVG. TVG automatically adjusts the gain with depth so that echoes of the same strength and different depths are shown in the same colors regardless of their depths. Do not set the TVG too high; close-range echoes may not be displayed

2.7.1 Setting for TVG level

Set-up for TVG level. Do not set the TVG too high; close-range echoes may not be displayed

□ Setting for low frequency TVG

menu → select [display] → select [TVG(L)] → select desired level

□ Setting for high frequency TVG

menu → select [display] → select [TVG(H)] → select desired level

2.7.2 TVG거리 Setting for TVG distance

TVG set up for applied distance.

□ Setting for low frequency TVG distance


menu → select [display] → select [TVG distance(low)] → select desired distance

□ Setting for high frequency TVG distance

menu → select [display] → select [TVG distance(high)] → select desired distance




< TVG level >



< TVG distance >

2.8 STC

This is useful to clear the surface of unwanted echoes to look for surface fish. The setting range is 0-10, and 0 is Off. In setting 10, STC deletes unwanted echoes from the surface to about 5m. Avoid setting the STC too high; fish echoes near the surface may be erased.



Setting for low frequency STC


menu → select [display] → select [STC(low)] → select desired value

Setting for high frequency STC

menu → select [display] → select [STC(high)] → select desired value

2.9 gain offset

If you want to increase or decrease the sensitivity or to control the sensitivity balance between low frequency and high frequency, you can set offset value. If sensitivity setting value is so small, weak signal is suppressed, then there's no image. If the values is so big, it will be difficult to identify the images because of noise. So you should control the gain.



Setting for low frequency gain offset


menu → select [display] → select [gain offset(L)] → select desired value

Setting for high frequency gain offset

menu → select [display] → select [gain offset(H)] → select desired value

2.10 Automatic gain offset

In automatic operation, seabed is automatically adjusted as reddish-brown color. You can modify offset value to set the sensitivity up or down in automatic gain. Clutter function operate automatically to eliminate small echo by dirt seawater and plankton. This allow good picture to identify.



Setting for auto gain offset of low frequency

menu → select [display] → [auto gain offset(L)] → select desired value

Setting for auto gain offset of high frequency

menu → select [display] → [auto gain offset(H)] → select desired value

3. Color

3.1 day/night


It can change the menu and background color of the screen. When you select day, the screen is bright and menu is white. When you select night, the screen is dark and menu is black.

☐ Setting for day/night


menu → select [color] → select [day/night] → select among 『day/night』

| | |
|--------------------|----------|
| 1.Day/Night | Day |
| 2.Colors | Night |
| 3.Hue | [A]Type1 |
| 4.Background | White |
| 5.Color Erase | 0% |
| 6.Clutter | 0% |
| 7.White Line | 0% |
| 8.White Line Color | White |
| 9.Temp. Color | White |

<day/night >



<day>



<night>

3.2 number of colors


It can select the number of colors

☐ Setting for number of colors


menu → select [color] → select [number of colors] → desired number of colors

| | |
|--------------------|-------|
| 1.Day/Night | Day |
| 2.Colors | 64 |
| 3.Hue | 16 |
| 4.Background | 8 |
| 5.Color Erase | 0% |
| 6.Clutter | 0% |
| 7.White Line | 0% |
| 8.White Line Color | White |
| 9.Temp. Color | White |

<number of colors>



<screen of 8 colors>



<screen of 64 colors>

3.3 hue

It can select the hue of pictures according to brightness and taste

tone

menu ➔ select [color] ➔ select [hue] ➔ select desired hue


| | |
|--------------------|-----------|
| 1.Day/Night | Day |
| 2.Colors | 16 |
| 3.Hue | [A]Type1 |
| 4.Background | [B]Type1 |
| 5.Color Erase | [S]Type1 |
| 6.Clutter | [S]Mono |
| 7.White Line | [S]Blue |
| 8.White Line Color | [S]Yellow |
| 9.Temp. Color | [S]Green |
| | [C]Type1 |
| | [C]Type2 |
| | [C]Type3 |

<hue>

3.4 background color

It can change background color according to the surrounding environment

| | |
|--------------------|------------|
| 1.Day/Night | Day |
| 2.Colors | 16 |
| 3.Hue | [A]Type1 |
| 4.Background | White |
| 5.Color Erase | Light Blue |
| 6.Clutter | Blue |
| 7.White Line | Deep Blue |
| 8.White Line Color | Black |
| 9.Temp. Color | White |



<background color>

<black>

<white>

Setting for background color

menu ➔ select [color] ➔ select [background] ➔ select desired color


3.5 Color erase

Needless dim noise can be eliminated by color erase


Because this function removes unwanted low level echoes off the screen by cutting them off, it is effective when the image is difficult to see because of interference or when you want to see only big fish school

Setting for color erase

menu ➔ select [color] ➔ select [color erase] ➔ select desired values (0 ~ 50 %)



<without color erase>




<removal of 50% color>

3.6 clutter


Clutter is used to eliminate low level return echoes because of dirt sea water etc. so one can see clear fish school.

Setting for clutter

menu ➔ select [color] ➔ select [clutter] ➔ select desired value (0 ~ 80%)



<without elimination of clutter>



<elimination of 40% clutter>

3.7 White line

White line allows you to identify easily between fish school on the bottom and seabed. The strong colors (seabed, big fish school, high density fish school) are displayed as white band, so it is not only helpful to identify seabed and fish school on the bottom but also in determining the density of fish. The setting range is from 0% to 100%.

☐ Setting for white line

menu ➔ select [color] ➔ select [white line] ➔ select desired color(0 ~ 100%)


3.8 Color of white line

It can change the color of white line.

☐ Setting for white line

menu ➔ select [color] ➔ select [white line] ➔ select desired color

| | |
|--------------------|--------------|
| 1.Day/Night | Day |
| 2.Colors | 16 |
| 3.Hue | [A]Type1 |
| 4.Background | White |
| 5.Color Erase | 0% |
| 6.Clutter | 0% |
| 7.White Line | 0% |
| 8.White Line Color | White |
| 9.Temp. Color | Blue |
| | Green |
| | Yellow-Green |
| | Yellow |
| | Orange |
| | Red |
| | Black |



<color of white line >

<without white line >

<white line 100%>


3.9 color of water temperature

Water temperature graph can be modified.

Setting for water temperature

menu ➔ select [color] ➔ select [temp. color] ➔ select desired color

| | |
|--------------------|--------------|
| 1.Day/Night | Day |
| 2.Colors | 16 |
| 3.Hue | [A]Type1 |
| 4.Background | White |
| 5.Color Erase | 0% |
| 6.Clutter | 0% |
| 7.White Line | 0% |
| 8.White Line Color | White |
| 9.Temp. Color | White |
| | Blue |
| | Green |
| | Yellow-Green |
| | Yellow |
| | Orange |
| | Red |
| | Black |



<Setting for color of temperature >

4. View

4.1 display direction

Select the display direction.

left : from right to left

right : from left to right

center : from center to two way left-right

| | |
|-------------------|--------|
| 1. Direction | Left |
| 2. Division | Center |
| 3. A-Scope | Right |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | Off |
| 7. Color Table | On |
| 8. Temp. Graph | Off |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | m |
| 12. Units(Temp.) | °C |
| 13. View Volt. | On |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |



☐ Setting for direction of display

menu ➔ select [view] ➔ select [direction] ➔ Select desired direction

4.2 Division

Select the division type for zoom and low/high frequency of screen

| | |
|-------------------|------------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Horizontal |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | Off |
| 7. Color Table | On |
| 8. Temp. Graph | Off |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | m |
| 12. Units(Temp.) | °C |
| 13. View Volt. | On |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |



<menu of split screen>

<vertical>


<horizontal>

☐ Setting for division

menu ➔ select [view] ➔ select [division] ➔ (select among 『vertical/horizontal』)

4.3 A-SCOPE

A-scope is the picture to show the strength of echo amplitude on the right side of the screen. As A-scope display big amplitude by big echo and small amplitude by small echo, it allows to identify easily small fish school, sea bottom and geology.



☐ Setting for A-Scope

menu ➔ select [view] ➔ select [A-Scope] ➔ (Select among 『Off/on』)

4.4 depth size


Change the font size of water depth at the left bottom of screen

| | |
|-------------------|----------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Off |
| 4. Depth Size | Off |
| 5. Depth Scale | 1 |
| 6. Help | 2 |
| 7. Color Table | 3 |
| 8. Temp. Graph | 4 |
| 9. Detection Area | 5 |
| 10. Header Info | Off |
| 11. Units (Depth) | m |
| 12. Units (Temp.) | °C |
| 13. View Volt. | On |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |


the

☐ Setting for depth size


menu ➔ select [view] ➔ select [depth size] ➔ select desired size



<small>



<middle>



<big>


4.5 depth scale

It can modify depth scale

□ Setting for depth scale

menu ➔ select [view] ➔ select [depth scale] ➔ select desired direction

| | |
|-------------------|----------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Off |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | Center |
| 7. Color Table | On |
| 8. Temp. Graph | Off |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | m |
| 12. Units(Temp.) | °C |
| 13. View Volt. | On |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |



4.6 help

It can select whether it will explain the selected item or not

| | |
|-------------------|------------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Off |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | Off |
| 7. Color Table | View |
| 8. Temp. Graph | Close(5'') |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | m |
| 12. Units(Temp.) | °C |
| 13. View Volt. | On |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |

| | | |
|------------|-------------------|----------|
| 1. SONAR | 1. Direction | Left |
| 2. DISP. | 2. Division | Vertical |
| 3. COLOR | 3. A-Scope | Off |
| 4. VIEW | 4. Depth Size | 3 |
| 5. ALARM | 5. Depth Scale | Right |
| 6. ETC | 6. Help | View |
| 7. ZOOM | 7. Color Table | On |
| 8. FISH | 8. Temp. Graph | Off |
| 9. NMEA | 9. Detection Area | Off |
| 10. Calib. | 10. Header Info | Off |
| | 11. Units(Depth) | m |
| | 12. Units(Temp.) | °C |
| | 13. View Volt. | On |
| | 14. Date/Time | Off |
| | 15. COG/SOG | Off |
| | 16. Lati./Longi. | Off |

help

▲/▼ : Move
▶/ENT : Ok
◀/MENU : Previous

□ Setting for help

menu ➔ select [view] ➔ select [help] ➔ (select among 『off/on/end(5 seconds)』)


- **Off** : Do not show help
- **On** : Show help
- **End(5 seconds)** : If there's no key control for 5 seconds, the help will be turned off automatically.

4.7 Color table

It can select whether it will show the color table on the right in the center of screen or not

Setting for color table

menu ➔ select [view] ➔ select [color table] ➔ Select among on/off




4.8 temperatures

It can select whether it will show water temperature or not. When displaying the temperature graph, choose the width of the scale in step 2. (narrow : 8°C, wide : 16°C). And it needs temperature sensor.

Setting for temperature

menu ➔ select [view] ➔ select [temperature] ➔ (select among 『off/on』)




4.9 detection area

It can select whether it will show the detection range or not

□ Setting for detection area

menu → select [view] → select [detection area] → (Select among on/off)




4.10 header info

It can select whether it will show the informations on top of the screen or not

□ Setting for information

menu → select [view] → select [header info] → (Select among [on/off])



4.11 Setting for unit

Depth : select depth unit

temperature : select temperature unit.

| | |
|-------------------|----------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Off |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | View |
| 7. Color Table | On |
| 8. Temp. Graph | Off |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | ft |
| 12. Units(Temp.) | m |
| 13. View Volt. | fa |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |

| | |
|-------------------|----------|
| 1. Direction | Left |
| 2. Division | Vertical |
| 3. A-Scope | Off |
| 4. Depth Size | 3 |
| 5. Depth Scale | Right |
| 6. Help | View |
| 7. Color Table | On |
| 8. Temp. Graph | Off |
| 9. Detection Area | Off |
| 10. Header Info | Off |
| 11. Units(Depth) | m |
| 12. Units(Temp.) | °C |
| 13. View Volt. | °F |
| 14. Date/Time | Off |
| 15. COG/SOG | Off |
| 16. Lati./Longi. | Off |

Setting for depth unit

menu ➔ select [view] ➔ select [unit(depth)] ➔ (Select among 『ft/m/fa』)

Setting for temperature unit

menu ➔ select [view] ➔ select [unit(temp.)] ➔ (Select among 『°C/ °F』)

5. Alarm

5.1 Setting for alarm

depth : when the depth is out of setting range, alarm alerts you.

temperature : when the water temperature is out of setting range, alarm alerts you.

Fish school :

When the fish school appear in setting range or all range from the surface of transducer to sea floor, alarm alerts you.

| | |
|-----------------|-------------|
| 1. Depth | Off |
| Min | 0 |
| Max | 1000 |
| 2. Temp. | Off |
| Min | 0 |
| Max | 30 |
| 3. Fish | Off |

❑ Setting for depth alarm

menu ➔ select [alarm] ➔ select [depth] ➔ (Select among 『off/on』)

setting for minimum depth

menu ➔ select [alarm] ➔ select [minimum] ➔ Select among 3~3000

setting for maximum depth

menu ➔ select [alarm] ➔ select [maximum] ➔ Select among 3~3000

❑ Setting for temperature

menu ➔ select [alarm] ➔ select [temperature] ➔ (Select among 『off/on』)

setting for minimum temperature

menu ➔ select [alarm] ➔ select [minimum] ➔ Select among 3~3000

setting for maximum temperature

menu ➔ select [alarm] ➔ select [maximum] ➔ Select among 3~3000

❑ Setting for fish school

menu ➔ select [alarm] ➔ select [fish school] ➔ (Select among 『off/on』)

6. ETC

6.1 Language

The Language menu selects the language to use

□ Setting for language

menu ➔ select [ETC] ➔ select [language] ➔ (Select among various languages)

6.2 sound of key beep

It can select whether it will ring or not.

□ Setting for key beep

menu ➔ select [ETC] ➔ select [key beep] ➔ select among 『off/on』

6.3 function key

There are Tx power, Tx Rate, Auto Gain, Display speed, Interference, Noise reduction, TVG, STC, Gain offset, Auto Gain offset, Hue, background, Zoom mode, Capture in the function keys. If the user register frequently used functions, the operation is simple. Function key is set to a TVG.

| | | |
|-----------|----------------|--------------|
| 1.SONAR | 1. Language | English |
| 2.DISP. | 2. Key Beep | Off |
| 3.COLOR | 3. Func Key | Tx Power |
| 4.VIEW | 4. Push Button | Tx Rate |
| 5.ALARM | 5. Simulation | Auto Range |
| 6.ETC | 6. Version | Disp. Speed |
| 7.ZOOM | 7. Reset | Interference |
| 8.FISH | | Noise Redu. |
| 9.NMEA | | TVG |
| 10.Calib. | | STC |
| | | Gain Offset |
| | | AG Offset |
| | | Hue |
| | | Background |
| | | Zoom Mode |
| | | Capture |

□ Setting for function key

menu ➔ select [ETC] ➔ select [func key] ➔ Select desired operation

6.4 Push Button

When the push button is off, Sensitivity will not be changed to automatic mode or manual mode regardless the user push the button for sensitivity adjustment.

❑ Setting for Push button

menu ➔ select [ETC] ➔Select [Push Button] ➔ (Select among 『on/off』)

6.5 Simulation

It can select whether it will activate the simulation mode or not

| | |
|-----------------------|---------|
| 1. Language | English |
| 2. Key Beep | Off |
| 3. Func Key | Capture |
| 4. Push Button | On |
| 5. Simulation | Off |
| 6. Version | Demo1 |
| 7. Reset | Demo2 |

❑ Setting for simulation

menu ➔ select [ETC] ➔Select [Simulation] ➔ (Select among 『Off/Demo1/Demo2』)

7. Zoom

7.1 Zoom mode

Select your desired zooming mode as follows;

| | |
|----------------------|---------------------|
| 1.Zoom Mode | Part |
| 2.Zoom Start | Fix Bottom |
| 3.Zoom End | Bottom Sedi. |
| 4.Zoom Length | 5m |

Setting for Zoom mode

menu ➔ select [user] ➔ Select [Zoom mode] ➔ Select your desired mode

7.2 Setting for zoom start

Select the starting point for partial zoom

Setting for starting point of partial zoom up

menu ➔ select [user] ➔select [zoom start] ➔ select between 3 and 3000m

7.3 Setting for zoom end

Select the ending point for partial zoom

Setting for ending point of partial zoom up

menu ➔select [user] ➔ Select [zoom end] ➔ select between 3 and 3000m

7.4 Setting for zoom length

Select the size of zoom length

Setting for zoom length

menu ➔ select [User] ➔ Select[zoom length] ➔ Select between 3 ~ 3000m(『3~3000m』)

8. Fish Schools

8.1 Display of fish schools

Display fish schools.

| | |
|----------------------|--------------|
| 1.View Fish | Off |
| 2.Fish Filter | Fish1 |
| 3.Fish Gain | Fish2 |
| | Fish3 |

Setting for display of fish schools

menu ➔ select [Fish] ➔ Select [view fish] ➔ Select your desired display mode

8.2 Fish Schools filter

Setting for fish schools filter.

| | |
|----------------------|---------------|
| 1.View Fish | Off |
| 2.Fish Filter | Low |
| 3.Fish Gain | Meduim |
| | High |

Setting for fish schools filter

menu ➔ select [Fish] ➔ Select [fish filter] ➔ Select your desired filter level

8.3 Fish Schools sensitivity

Setting fish schools sensitivity.

| | |
|----------------------|---------------|
| 1.View Fish | Off |
| 2.Fish Filter | Meduim |
| 3.Fish Gain | Low |
| | Meduim |
| | High |

Setting for fish gain

menu ➔ select [Fish] ➔ Select [fish gain] ➔ Select desired sensitivity level

9. NEMA

9.1 NEMA Output

It will transmit DPT etc (ex water depth).among the standard of NMEA0183 through RS-232C port. It will transmit RS-232C once it is off.

| | |
|--------------------|------------|
| 1.NMEA Output | Off |
| 2.NMEA Output Data | UART1 |
| 3.NMEA Input | UART2 |
| 4.UART1 | 4800 |
| 4.UART2 | 4800 |
| 6.Local offset | +9 |
| 7.Time format | 24 hours |
| 8.Date format | yyyy.MM.dd |
| 9.UART Monitor | |

Setting for NMEA output

menu → select [NEMA] → Select [NMEA output] → Select among OFF/UART1/UART2

9.2 UART1

Among RS-232C port from the main unit, it will transmit DPT to NMEA1 port and receive GPS data. Speed can be set up with 4800, 9600 or 38400

| | |
|--------------------|------------|
| 1.NMEA Output | UART2 |
| 2.NMEA Output Data | UART1 |
| 3.NMEA Input | UART1 |
| 4.UART1 | 4800 |
| 4.UART2 | 9600 |
| 6.Local offset | 38400 |
| 7.Time format | 24 hours |
| 8.Date format | yyyy.MM.dd |
| 9.UART Monitor | |

Setting for UART1

menu → select [NEMA] → Select [UART1] → Select among 『4800/9600/38400』

9.3 UART2

Among RS-232C port from the main unit, it will transmit DPT to NMEA2 port and receive GPS data. Speed can be set up with 4800, 9600 or 38400

Setting for UART2

menu → select [NEMA] → select [UART2] → (select among 『4800/9600/38400』)

9.4 Monitor UART

Both of RS-232c port can be monitored

Access UART monitor

menu → select [NEMA] → Select [UART monitor] → To return press [menu]

10. Modification

10.1 Temperature

Water temperature can be modified from -3 to +3

Setting for temp modification

menu ➔ select [calib.] ➔ Select [temp.] ➔ Select from -3 to +3

10.2 Voltage

Voltage can be modified from -3 to +3

Setting for voltage modification

menu ➔ select [calib.] ➔ select [voltage] ➔ (select among 『-3~ +3』)

10.3 Beam angle

Beam angle is frequency angle from transducer. Low frequency can detect wide area and higher frequency can detect lower area. Beam angle can be modified from 4° to 26°

Depending on beam angle, receiving radius of bottom can be displayed on A-Scope and receiving radius can be changed depending on type of beam angle.

Setting for low frequency beam angle

menu ➔ select [calib.] ➔ select [beam angle(LF)] ➔ select among 『4°~ 26°』

Setting for high frequency beam angle modification

menu ➔ select [calib.] ➔ select [beam angle(HF)] ➔ select among 『4°~ 26°』

5

Connecting other devices



This chapter will explain the maintenance and defectiveness of SDF-310

- Installation**
- Cable connection by the display**
- Connector pin arrangement from the back panel**
- Power supply connection**


1. Installation

Installation of display bracket

- 1 Locate the bracket mounting on a proper location.
- 2 Hold the display unit and fix it with bolts
- 3 Insert bracket mounting bolts gently.


Separate display from bracket.

- 1 Switch off the device
- 2 Unwind bracket mounting bolts.




2. Cable connection

Connect power supply and transducer to the proper connector.



3. Rear connector pinout

Pin position at the back of the transmission indicator.



ETHER NET


- ② COMMON_1
- ③ TD+
- ④ GND
- ⑤ EXT_ON/OFF
- ⑥ NC
- ⑦ NC
- ⑧ NC
- ⑨ RD-
- ⑩ COMMON_2
- ⑪ TD-
- ⑫ GND
- ⑬ NC
- ⑭ NC
- ⑮ NC

NAME1/ALARM




- ① GND
- ② GND
- ③ NMEA_IN
- ④ NMEA_OUT
- ⑤ NC
- ⑥ ALARM
- ⑦ ALARM_GND

TRANSDUCER



- ① TEMP1
- ② TD_L+
- ③ TD_H+
- ④ TD_GND
- ⑤ TD_L-
- ⑥ TD_H-
- ⑦ TEMP2
- ⑧ NC

POWER (DC12/24)



- ① PWR+
- ② EARTH
- ③ PWR-


NAME2/SENSOR



- ① GND
- ② GND
- ③ NMEA_IN
- ④ NMEA_OUT
- ⑤ SPEED SUPPLY
- ⑥ SPEED
- ⑦ TEMP
- ⑧ GND

. Connecting power cable

POWER connector on the back of the display is connected to the power cable.



EARTH

- ① Please use a thick cable of earth
- ② Please let the ground and earth in a shortest distance

6

Maintenance/troubleshooting



This section describe the maintenance and trouble-shooting of SDF-310.

- **System maintenance and repair**
- **Trouble-shooting**

1. System maintenance and repair

Regular maintenance and repair is essential for good performance.

Maintenance of equipment refers to the regular inspection of equipment and the software upgrade and the following items should be included.

| Item | Action |
|--------------------------------------|--|
| Connector and terminal | ✓ Please check the connector and terminal on the back of the display for proper connection. |
| Cable | ✓ Check each cable and if the cable is damaged or blown, replace it immediately. |
| Earth terminal and Earth line | ✓ Check earth terminal. If the ground terminal is rust of rot, replace or clean state And check the connection of earth line also. |
| Maintain cleanliness | ✓ Dust or dirt on the LCD can be removed with a tissue or LCD cleaner, and wipe carefully to prevent scratching. Do not use solvents such as thinner, acetone or benzene to clean the unit. They can remove paint and marking. |

2. Troubleshooting

The table describe the symptom of trouble and their trouble-shooting. If the repair isn't possible by general remedy, do not attempt to check inside of equipment. If the inspection and maintenance is wrong, it can degrade the performance of equipment. So all repair works should be left to AS technician.

A/S Technician ☎ : 1577~0198


| Symtom | Remedy |
|--|---|
| The power does not turn-on | <ul style="list-style-type: none"> ✓ Power connector ✓ Power supply and Fuse ✓ Voltage of battery (under DC 12V) ✓ Polarity of the power, + - |
| Screen is not turned on or too dark | <ul style="list-style-type: none"> ✓ Screen brightness is 1 ✓ Display is night mode |
| Screen flicker or white lines Change of screen color | <ul style="list-style-type: none"> ✓ Contact of LCD connector ✓ Cleanness around LCD connector |
| Fish school isn't display on the screen | <ul style="list-style-type: none"> ✓ Poor contact of transducer connector and corrosion ✓ Transducer is under water |
| Sensitivity is low | <ul style="list-style-type: none"> ✓ If TVG, STC set-up is too high, you can increase the gain and then decrease TVG, STC. ✓ If the the value of clutter and color erase are too high, decrease them. |
| Several seabed | <ul style="list-style-type: none"> ✓ If the depth is too low or sensitivity is too high, you can control the gain by repeat of sound wave ✓ Low Tx Speed |
| Record of Fish school and sea bottom isn't stable | <ul style="list-style-type: none"> ✓ Because of vessel's rolling, pitching, bubbles by vessel's screw and front vessel can induce them |
| No oscillation line | <ul style="list-style-type: none"> ✓ Set-up shift '0' |

Appendix



This section describe the appendix related to the equipment operation of SDF-310

Product outline drawing



| Revision History | | | |
|------------------|------|-------------|------|
| No. | Loc. | Description | Date |
| | | | |

Note
1.

| | | | | | | | |
|-------------------|------------|--------------|-----------|---------------------|-------------|----------|--------|
| No. | 1 | SDF-310 ASSY | Part Name | 1 | NO9-2000-00 | Part No. | Remark |
| List of component | | | | | | | |
| Date | 10/28/2013 | | | | | | |
| Design (Inet) | R&D | | | | | | |
| Approved | J. S. PARK | | | | | | |
| Checked | J. S. JEON | | | | | | |
| Designed | J. S. JEON | | | | | | |
| Q'ty | 1 EA/SET | | | | | | |
| Scale 1:1 | Unit | mm | ft | kg | A2 | | |
| TITLE | | | | SAMYUNG ENC | | | |
| SDF-310 외형도 | | | | Ino No. NO9-2000-00 | | | |
| 1 | | | | 1 of 1 | | | |

| | | | |
|------------------|-------------------|----------------|---------------|
| Substitute | General Tolerance | Angle | Fraction |
| | ±0.2 | ±1.0° | ± 1/5 |
| Original Drawing | Material | Heat treatment | Adoption Item |
| | | | Stock No. |

NO9-2000-00