N13.430 CR2 Specifications



317 kW [431 hp]
13.6 l [830 in³]
6 cylinders in line
4 stroke Diesel
132 x 165 mm [5.2 x 6.5 in]
16:1
1800 rpm
600 rpm
2328.6 Nm
1300 rpm
1380 kg [3042 lbs]

Engine base	John Deere
Fuel system	Electronically controlled unit injectors
Air intake	Turbocharged Air-to-seawater aftercooler
Cooling	Closed cooling with heat exchanger
Max mounting angl	e 0° Front up 12° Front down
Alternator	24 Volt 100 Amp
Rating	M1
Emission complian	ce IMO Annex VI compliant EPA marine Tier 3 NRMM 97/68/EC



N13.430 CR2

317 kW [431 hp] at 1800 rpm

TECHNICAL DESCRIPTION

Engine block

- Replaceable wet-type cylinder liners
- 4 valves per cylinder
- Watercooled exhaust manifold

Fuel system

- Electronically controlled unit injectors
- Primary & secondary fuel filter

Lubrication system

- Replaceable full-flow oil filter
- Oil dipstick
- Oil cooler

Cooling system

- Closed cooling with heat exchanger
- Gear driven self-priming raw water pump
- Coolant circulating pump
- Water cooled exhaust elbow

Electrical system & Instrumentation

- 24V 100A alternator
- 24 Volt starter motor
- Complete instrumentation including key switch and alarms
- Extension cable harness with plug-in connection

Air intake

- Water cooled turbocharger
- Air-to-Coolant aftercooler

Other features

- Flywheel SAE 1
- Damper pulley
- Flexible engine mounting

Optional equipment & accessories

- Keel cooling adaptation
- Dry exhaust elbow
- Complete marine propulsion systems
- Marine transmission adaptation kits
- Throttle and shift controls
- Additional instrumentation, Flying bridge extension harness
- Rigid engine mounting
- Power take off
- Type approval

RATING


- 24 daily operating hours
- Load factor over 65%
- Uninterrupted full power

TRANSMISSIONS


Contact your local dealer for more details and availability for transmission model and type.

PERFORMANCE CURVES


Power at crankshaft



Torque at crankshaft



Fuel consumption



Nanni Industries S.A.S. France